Component	Description & Use	Colour Finish	Code
	Thin lining sheet Plain Colour or Wood grain finish matches composite panels 2440 x 1220 mm sheet 3 mm nominal thickness	Glacier White Polygloss Satin White	T204
	Use: Wall and ceiling lining	Chalk	
		Cameo	
		Divine Oak	
		Hamilton Oak	
		Coastal Elm	
	White Acrylic thin sheet 1220mm x 2000mm x 2mm Use: For shower wall lining.	White Acrylic	
	Shower door up to 650mm wide	White or annodised alum Frame	

Component	Description & Use	Colour Finish	Code
	Thin Sheet Jointer 3mm 2.4 metre lengths rigid extrusion matching colour for Duralite® panel Use: Straight jointer between two 3.6mm thin	White	P567
	wall / ceiling panels	Chalk	
	Thin Sheet End Cap 3mm 2.4 metre lengths rigid extrusion matching colour for Duralite® panel Use: Trim ming edges of 3mm thin sheet	Tan White Chalk Cameo	P268
		Tan	

	Thin Sheet Internal corner 3mm 2.4 metre lengths rigid extrusion matching colour for Duralite® panel Use: 90° jointer for thin sheet internal corner only	White Chalk Cameo Tan	P266
Component	Description & Use	Colour Finish	Code

Component	Description & Use	Colour Finish	Code
	Duralite® Composite Panel		D101
	Plain Colour or Wood grain Finish 1220 x 2440 mm sheet	Glacier White	
	19.8mm nominal thickness	Hamilton Oak	
	Use: The construction panel for internal walls and cabinetry	Divine Oak	
		Coastal Elm	
		Polygloss	
		Satin White	

Component	Description & Use	Colour Finish	Code
	Set A - Corner Base 90° Corner Jointer 2.4 metre lengths rigid extrusion (requires P522 to complete set)	Natural	P467
	Use: Right Angle Connector for Duralite® Composite panels and décor trim		
	Set A - Décor Corner Trim		P522
	2.4 metre lengths rigid extrusion matching colour for Duralite® panel (requires P467 to complete set	White	
		Tan	
	Use: Cover cap for 90° corner jointer P467		
	Composite Panel Jointer 45°		P545
	2.4 metre lengths rigid extrusion matching colour for Duralite® panel	White	
	Use: 45° jointer between panels, external and internal corners.	Tan	
	90° Overlay Corner		P757
• 1	2.4 metre lengths rigid extrusion matching colour for Duralite [™] panel	White	
Y	Use: Forms an external 90° corner trim. Allows for one panel to be overlaying and one panel to butt at 90°	Tan	

Duralite Modular Systems Parts List

	Edge Cap Self Adhesive 45 metre roll flexible extrusion matching colour for Duralite® panel Purchased per metre Use: Flexible edge trimming for Duralite® Composite Panel D101.Trims openings and shaped edges	White Tan	P341
--	--	--------------	------

Component	Description & Use	Colour Finish	Code
	Ceiling - Base		P469
	2.4 metre lengths rigid extrusion	Natural	
	Use: To connect Duralite® panels to ceiling or		
	floor – see manual for each use.		
	Double Ceiling – Base	Natural	P468
	Décor Base Trim		P336
	20 metre rolls flexible extrusion matching colour		
	for Duralite® panel	White	
	Purchased per metre		
	Use: Knock in cover for P469	Tan	
	U Channel		P466
	2.4 metre lengths rigid extrusion matching	White	
	colour for Duralite® panel		
	Use: Rigid end finishing trim for Duralite®	Tan	
	composite panel		
	F Channel		DEGA
			P521
	2.4 metre lengths rigid extrusion matching colour for Duralite® Composite Panel	White	
		vviiite	
	Use: Rigid end cap with connector. Connecting	Tan	
	panels to floor, walls and bench tops. Shelving edge.		
			D
	Composite Panel Jointer		P558
4/10	2.4 metre lengths rigid extrusion matching colour for Duralite® panel	White	
	·	_	
	Use: Straight jointer between two Duralite®	Tan	
1114276	composite panels		

Component	Description & Use	Colour Finish	Code
	Edge Tape 24mm Glued		PG725
	50m roll glued 24mm tape. Colours matched to panels	White	
	Use : For edge banding Duralite™ Composite	Divine Oak	
	Panel D101	Hamilton Oak	
	24mm x 2mm – edgeband machine	Coastal Elm	
	Also available		
	22mm x 1mm – iron on – all colours		

Component	Description & Use	Colour Finish	Code
	Screws: 6g 12mm mushwas pozi drive self tapers (Packs per 200) Use: Screws for attaching Duralite® components to walls, ceilings, catch plate, utility plate and Duralite® panels	Zinc	S612
Dummin Park	Screws: 6g x5/8 counter sunk pozi drive (packs per 100) Use: For push locks	Zinc	S615
S. Tamamanana	Screws: 8g 30mm mushwas pozi drive self tapers (packs per 100) Use: Screw for attaching catch block to Duralite® composite panels	Zinc	S830
Summer of the second	Screws: Drawer Rails through 8mm spacer (packs per 100) Use:- Drawer Rails	Zinc	S620
	Silent Bumper (100 per sheet) Use: Fix to door as soft buffer.	Clear	B200

Component	Description & Use	Colour Finish	Code
	Corner block Use: For connecting shelving and some panel components	White	CBL44

Component	Description & Use	Colour Finish	Code
	Ceiling Bracket Duralite® Use: Anchor to hold ceiling base P469 in place	Stainless Steel	B881
	Corner Clip HM Template Use: Attach at base on corner for P336 to fit neatly on corners	Natural	C642
	Cable Tube (10mtr pack) Use: To provide conduit for 12volt wiring through VHD poly in composite panel	Green	C500
	Hollow wall anchor plus screw For drawer fronts and spring lifters on overhead cupboards		HWA-M4
			<u> </u>
	Cup hinge with mount - 110 full overlay Cup hinge with mount - 110 half overlay		CH107 CH102

Component	Description & Use	Qty per set	Code
E.A.	Door Hinge Duralite® (H202) Nickel – silver colour only		
	Use: Doors and cupboards	1 x Hinge	H202
	Hinge Base Plate Duralite®	1 x Base plate	
Component	Use: Anchor for S510 screws hinges in panel	Colour Finish	Code
Component	Description & Us	Colour Finish	Code
	Ali Rail – 2.4m lengths		
	Use: For top cabinet rail and drawer catches	Aluminium	DRLB2.4

Component	Description & Use	Qty per set	Code
	Spring Lift up sml (GSTY) Use: For lift up cupboard doors		SLFT
	Catch Block Duralite® (B102) Use: To support the utility plate bracket	1 x spring lift up 1 x Catch block 1 x Utility plate	
	Utility Plate Bracket Duralite® (U456) Use: Fixes to catch block and can support the spring lift up stay		

Component	Description & Use	Qty per set	Code
	Single Push lock 19mm (L161) Use: Lock for cupboards and drawers. Push Lock Button (L190) Use: Opener for Push Lock L161 Push Lock Rosette (L191) Use: Trim for Push Lock Button L190 Catch Block Duralite® (B102) Use: To support the catch plate for push lock. Catch Plate (C751) Use: Door lock catch in cupboards and drawers	1 x push lock 1 x push lock button 1 x push lock rosette 1 x catch block 1 x catch plate	L161s
	Double Double sided Pushlock (L161DLW) Use: For shower door *Other components to the double set are the same as for the single set, with a slight variance in quantity of some of the componentry.	1 x dbl push lock 2 x push lock button 1 x push lock rosette 1 x catch block 1 x catch plate	L160D

Component	Description & Use	Qty per set	Code
	Drawer Sides (pair) Use: Metal sides for draw, set includes slide rail – Low = 86mm high sides Med = 118mm high sides High = 150mm high sides Drawer Front Fix Bracket (L & R) x 1 Use: Comes with drawer side. Connects drawer front with hollow wall anchors	1 x pair drawer sides 1 x pair Front fix bracket (L&R) 8 x hollow wall anchor and screw	
	Hollow wall anchor (8 per drawer) Use: Fixing drawer runners to cabinet sides Drawer front to front fix bracker.		

Component	Description & Use	Colour Finish	Code
C	Hollow wall anchor setting tool		HWA-TG
	Tamper Block Duralite® Use: Wooden knock in used to knock P336 into P469		TB456
	Jig Drilling Guide Duralite® Use: Template for drilling holes for hinge base plate H100		JD630
	Scribing Tool Duralite® Use: Marking out shape on P336 for internal corner		SC001

Duralite®

Duralite Modular Systems Parts List

Component	Description & Use	Colour Finish	Code
	Tecni Seal Silicone Sealant 300 ml cartridge		TS32
	Use: Filler to match Duralite® décor trim	Tan	
		White	

Component	Description & Use	Colour Finish	Code
EN HI EN	*Simson Adhesive (white) Cartridge 290ml Use: Contact adhesive for joining and securing Duralite® components. For gluing thin sheets to walls and ceiling	White	S703

*Duralite® System Construction (CD	MAN101CD
only) available with order	

Duralite® Modular Systems

Phone: 07 868 8813 NZ
Phone 041 887 6625 AUST
Email: info@duralitesystems.co.nz
info@duralitesystems.com.au
New Zealand Patent No. 542756

International Patent No. PCT/NZ2006/000011 Australian Patent Application No. 2006295511

